



4. It will take up to 24 hours for the beads to fully absorb the water, however the unit may be used immediately. The beads are refillable, but should be replaced at least one time per year.
5. For best efficiency, base should be about  $\frac{3}{4}$  full with water beads or a combination of both, but never overfilled (blocks airflow).

### USING YOUR CIGAR OASIS MAGNA 3.0

- Once the unit is put together and plugged in, it turns on after a few seconds of powering up and then it will read the current humidity. The unit is factory preset at 70% humidity. As soon as the humidity drops below 70% the fan will come on to add moisture to the humidor.
- To raise or lower the humidity settings use the **UP** or **DOWN** arrows.
- When the unit needs to be refilled with distilled water, the **Low Water** and **Alert** icons will flash on display.  
- When the base is refilled and the unit gets to the setpoint the icons will shut off.

### PLACEMENT

It is best to place the Cigar Oasis with the rear air vents facing the back wall leaving about two inches for air to travel upward. Keep the back wall clear of any boxes to allow air to flow freely and never block or cover the vent.

### ASSEMBLY & STARTING YOUR CIGAR OASIS MAGNA 3.0

1. Remove all contents from the box.
2. Remove the white plastic cap from the front of the unit.
3. Locate the water beads and pour through the hole into the white water tank. Fill the water tank up to the bottom of the vertical lines using **distilled** water only.
4. Place the white plastic cap over the hole in front of the unit.
5. Plug the micro USB connector **A** into the side of the Cigar Oasis Magna 3.0 unit and then plug the adapter into the wall to power up the unit. **Only use the supplied power adapter.**
6. Locate the remote inside the cabinet and plug into the unit.

### WATER TANK REFILL INSTRUCTIONS

1. Remove the white plastic cap from the front of the unit.
2. Pour **distilled** water through the hole into the water tank.
3. Replace the white plastic cap over the hole in front of the unit.

### Change Temperature Between Fahrenheit and Celsius

- 1) Hold the **CIRCLE** button until the **F** or **C** start flashing.
- 2) Press the **UP** arrow to select Celsius or Fahrenheit.
- 3) Hold the **CIRCLE** button down until **F** or **C** stop flashing to save the changes.

### Calibrate Humidity

- 1) Hold the **CIRCLE** and **UP** arrow until the screen displays **U**.
- 2) Use **UP** and **DOWN** arrows to raise or lower humidity +/-9%.
- 3) Hold the **CIRCLE** and **UP** arrow to save the changes.

### Optional Accessories

**Circulation Fans** - Plug the fan cable into the Micro USB port on the unit and then plug the power cord into the Y cable of the fans. Locate the fans at the furthest point possible in the humidor from the water tank. Face them towards the middle of the humidor at a 45 degree angle / \.

# CIGAR OASIS

## MAGNA 3.0



For warranty information go to [www.cigaroasis.com](http://www.cigaroasis.com).



79 Heisser Court  
Farmingdale, NY 11735  
516.520.5258  
[www.cigaroasis.com](http://www.cigaroasis.com)

*Cigar Oasis...the best in cigar humidification just got even better!*